



ProTechⁱ Series

Advanced Electronic, Fully Automatic 4-Stage On-Board Marine Battery Charger

▶ Distributed-On-Demand™ Technology

Automatically senses and distributes up to 10 amps to any one bank or combination of all banks.

▶ Fully Automatic 4-Stage Charging

Extend battery life and usage with multi-stage charging: fast charge, conditioning, and float/maintenance mode, safe for long and short term storage. Automatic dockside power mode for 12 Volt DC lighting and appliances.

▶ Auto Ranging AC Input

Fully automatic global AC input 95 to 250 VAC 50/60 HZ.

▶ Fast & Easy Setup

Select performance charge profiles for Flooded (lead-acid), AGM or GEL cell batteries. Program your ProTech charger for conditioning modes of 1 to 4 hours.

▶ Compact Aluminum Housing

For superior heat transfer and durability.

▶ Built-In Quality & Safety

Marine rated with safety features that include: over temperature, over voltage, overload, reverse polarity and ignition protection.

▶ LED Status Center

Provides at-a-glance status of fast charge, conditioning, ready (float/maintenance) and battery type selection.

Compact Advanced Electronic Technology with Hi Line Feature Set



Fully Automatic 4-Step Charging

The ProTech i-Series is designed to deliver performance and value by employing proven advanced electronic technology with added innovative styling and features like: fully automatic wide range global AC input, user programmable battery type selector and active battery balance control on select models.

Specifications

model	part no.	volts	amps	banks	AC input	cycle	size	weight
ProTech1210i	63310	12	10 Amp	2 Bank	95-250	50/60	10" (l) x 6.188" (w) x 2.875" (h)	4 lbs
ProTech1215i	63315	12	15 Amp	3 Bank	95-250	50/60	10" (l) x 6.188" (w) x 2.875" (h)	4 lbs
ProTech1220i	63320	12	20 Amp	3 Bank	95-250	50/60	10" (l) x 6.188" (w) x 2.875" (h)	4 lbs
ProTech1225i	63325	12	25 Amp	3 Bank	95-250	50/60	10" (l) x 6.188" (w) x 2.875" (h)	4 lbs
ProTech1230i Plus	63331	12	30 Amp	3 Bank	95-250	50/60	15.5" (l) x 7.188" (w) x 2.875" (h)	6.5 lbs
ProTech1240i Plus	63341	12	40 Amp	3 Bank	95-250	50/60	15.5" (l) x 7.188" (w) x 2.875" (h)	6.5 lbs
ProTech2420i Plus	63420	24	20 Amp	3 Bank	95-250	50/60	15.5" (l) x 7.188" (w) x 2.875" (h)	6.5 lbs